


Tilting centrifugal dryers series LR tougher and less smooth operation

Main uses


- drying metal and plastic articles by centrifuging in forced warm air
- it is used for not excessively delicate products where no pickling or polishing is required, easily obtainable with the ASC 100-350-550 machines.

Main characteristics

- robust yet easy to handle structure with innovative aspects
- unloading and tilting action through a lever
- non-removable basket in drilled AISI 304 stainless steel, hole dia 2 mm (0.9 mm on request)
- control panel with cycle timer, centrifugation switch and heating switch.



Stainless steel
drilled \varnothing 2 mm



Stainless steel
drilled \varnothing 0,9 mm



Tilting centrifugal dryers at 180°

DRYER	ASC 50 / LR	ASC 70 / LR
Internal basket dimensions: \varnothing x H (mm)	460 x 250	550 x 320
Theoretical volume (litres)	44	76
Capacity (kg)	40	60
Rpm	550	550
Heating elements (W)	2.500	3.000
Motor power (W)	750	1.500
Total installed power (W)	3.250	4.500
Overall dimensions B x D x H (mm)	970 x 780 x 1.050	1.110 x 830 x 1.200
Discharge opening B x D x H (mm)	680 x 460 x 380	760 x 520 x 400
Weight (kg)	200	285